

KAROLAM CEILING TILE

Light weight gypsum ceiling tiles with high surface quality, front face is covered with white PVC and back face with aluminium sheet. It can be also be produced as moisture resistant gypsum board type upon request.

- Moisture resistance
- Easy to clean
- Dry and easy application
- Time saving

Standards referred to (Board Type)

TS EN 14190

Fields of Application

Modular suspended ceilings

Storage

- Packages should be carried carefully.
- Packages should be kept on dry, clean and smooth surfaces.
- Avoid water contact.

General Properties

Board Type	Thickness (mm)	Weight (kg/m²)	Width (mm)	Length (mm)	Packaging (pcs.)
White Karolam (with folio)	8	7- 8			12
	9,5	7-8			10
White Karolam (without folio)	8	7-8	600	600	12
	9,5	7-8			10
White Karolam with Rough Surface	8	7-8			12
	9,5	7-8			10
White Karolam with Grizzeled Surface	8	7-8			12
	9,5	7-8			
WR White Karolam	9,5	~ 8			10
WR White Karolam with Grainy Surface	9,5				
WR White Karolam with Grizzled Surface	9,5	1			

Technical Properties

	8 mm	9,5 mm	
Bending tensile strength - longitudinal direction (N)	-	≥ 400	
Flexural breaking load - transverse direction (N)	-	≥ 160	
Water vapour diffusion resistance µ	10		
Thermal conductivity λ (W / mK)	0,25		
Width tolerance (mm)	0, -4		
Length tolerance (mm)	0, -5		
Thickness tolerance (mm)	± 0,5		
Angularity tolerance (mm)	≤ 2,5		
Edge Type	Square edge (SE)		

System Performances

System performance values e.g. sound insulation, fire resistance etc. depends on the mentioned system and it's components which are used or recommended by Knauf. For more details visit, http://www.eteknik.knauf.com.tr, http://www.knauf.com.tr/sistemler.asp, http://www.knauf.com.tr/kataloglar.asp

Ordering Terms

Minimum order quantity is 1 package. Please contact sales department for available product sizes other than the ones given on the table.

For quality certificates visit: http://www.knauf.com.tr/kalitebelgeleri.asp For recommended price list visit: http://www.knauf.com.tr/fiyatlistesi.asp